

PRODUCT-DETAILS

DSH201 C16 AC30 DSH201 C16 AC30 Residual Current Circuit Breaker with Overcurrent Protection



| General Information | |
|-----------------------|---|
| Extended Product Type | DSH201 C16 AC30 |
| Product ID | 2CSR255070R1164 |
| EAN | 8012542353812 |
| Catalog Description | DSH201 C16 AC30 Residual Current Circuit Breaker with Overcurrent Protection |
| Long Description | protection against indirect contacts and additional protection against direct contacts. |

| Technical | |
|---------------------------------|--|
| Standards | IEC 61009-1 EN 61009-1 IEC 61009-2-1 EN 61009-2-1 |
| Tripping Characteristic | С |
| Type of Residual Current | Type AC |
| Rated Operational Voltage | acc. to IEC 60898-1 230 V |
| Dielectric Test Voltage | 2 kV |
| Input Voltage Type | AC |
| Rated Current (I _n) | 16 A |
| Rated Residual Current | 30 mA |
| Rated Short-Circuit Capacity | 6 kA |

DSH201 C16 AC30 2

| Rated Ultimate Short- Circuit Breaking Capacity | 10 kA | | |
|--|---|--|--|
| (I _{cu}) | | | |
| Rated Conditional Short-Circuit Current ($I_{\rm nc}$) | 10 kA | | |
| Maximum Surge Current | 0 kA | | |
| Leakage Current Type | AC | | |
| Frequency (f) | 50 Hz | | |
| Rated Frequency (f) | 50 Hz | | |
| Power Loss | Average per Pole 2.3 W Phase Pole 3.4 W Neutral Pole 1.2 W Total 4.5 W | | |
| Power Supply Connection | Arbitrary | | |
| Electrical Endurance | 10000 cycle | | |
| Mechanical Endurance | 20000 cycle | | |
| Number of Protected Poles | 1 | | |
| Number of Poles | 2 | | |
| Operating Characteristic | Instantaneous | | |
| Overvoltage Category | III | | |
| Position of Neutral Terminals | Right | | |
| Accessories Available | No | | |
| Connecting Capacity | Busbar 10 mm² Rigid 25 25 mm² Flexible 25 25 mm² | | |
| Material Compliance | | | |
| RoHS Information | 9AKK107492A2001 | | |
| RoHS Status | Following EU Directive 2011/65/EU | | |
| RoHS Date | 20190328 | | |
| REACH Declaration | 9AKK108467A9482 | | |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 | | |
| Environmental | | | |
| | Operation -25 55 °C | | |
| Ambient Air Temperature Degree of Protection | Operation -25 55 C | | |
| · · | | | |
| Pollution Degree | 2 | | |
| Dimensions | | | |
| Width in Number of Modular Spacings | 2 | | |
| | | | |

Product Net Width

Product Net Height
Product Net Depth /
Length

Product Net Weight

0.035 m 0.085 m

0.069 m

0.182 kg 69 mm DSH201 C16 AC30 3

Built-In Depth (t₂)

| _ | | | | |
|---|----|--------|-----|----|
| 1 | rA | \sim | rır | ~ |
| v | rd | CI | ш | ıu |
| | | | | |

Package Level 1 Units box 1 piece
Package Level 1 Gross
Weight

0.207 kg

Certificates and Declarations

Declaration of Conformity 9AKK107492A2001
- CE

Installation

Instructions and Manuals 9AKK1074920470

Popular Downloads

Data Sheet, Technical 9AKK107492A1478 Information

Classifications

| Object Classification Code | F | |
|----------------------------|--|--|
| eClass | V11.0 : 27142207 | |
| CN8 | 85363010 | |
| WEEE B2C / B2B | Business To Consumer | |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) | |
| ETIM 9 | EC000905 - Earth leakage circuit breaker | |
| ETIM 8 | EC000905 - Earth leakage circuit breaker | |

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \to\ Modular\ DIN\ Rail\ Products\ \to\ Residual\ Current\ Devices\ RCDs\ \to\ Residual\ Current\ Circuit\ Breakers\ with\ Overcurrent\ Protection\ RCBO$

DSH201 C16 AC30 4

